



**SPECIFICATION SHEET**

**PRODUCT: SL-100WBT**

*General Purpose HVAC Media*

**I. PERFORMANCE DATA \***

**Approximate Clean Resistance to Airflow**

<u>Velocity ( fpm )</u>	<u>Resistance ( "wg )</u>
100	0.030
200	0.080
300	0.145
400	0.220
500	0.305

**Average ASHRAE 52.1 Dust Holding Capacity (24" x 24"):** 150 - 200 g

**II. CONSTRUCTION**

**Multi-Denier, Single Layer Polyester**

**Nominal Thickness: 1"**

**Air Laid, Light Tack, Antimicrobial**

**Color: WHITE / BLUE**

**Master Roll Size: 87" wide x 90' long\*\***



**III. CLASSIFICATION / CERTIFICATION**



AIR FILTER UNIT  
AS TO FLAMMABILITY ONLY  
838H

**This filter meets GACT for sources subject to SUBPART HHHHHH  
(Paint Stripping and Miscellaneous Surface Coating at Area Sources) and SUBPART XXXXXX  
(Area Source Standards for Nine Metal Fabrication and Finishing Source Categories)  
(≥98% EFFICIENT when tested by ASHRAE Method 52.1 in accordance with the NESHAP)**

\* Note: Tests were conducted using Modified ASHRAE STANDARD 52-1 test apparatus and procedures (1.0" wg test endpoint). Actual resistances, arrestances, and holding capacities may vary in the field due to site-specific conditions.

\*\* ALSO AVAILABLE: Slit-To-Order Widths, Perforated-to-Order Lengths, and Cut Pads.